

LED Group

 Western Retail Park
 Nangor Road
 Dublin 12
 Ireland

 T +353 1 709 9000
 F +353 1 709 9060
 IRL Freefax 1800 281 282
 UK Freefax 0800 973 221

 Email info@ledgrouprobust.com
www.ledgrouprobust.com
www.robustdirect.com

ULTIMUM+ tilt 6W CCT4 LED fire rated downlight – Dimmer Compatibility List

Product Code: RULT06X4-01

Updated: 18.05.2021



#	Dimmer	Range	Result
1	ROBUS RLA400DT 5W Min 150W Max	15% - 80%	Compatible
2	ROBUS R10012G2W 3W Min 100W Max	10% - 100%	Compatible
3	ROBUS RLA200DTG 3W Min 133W Max	20% - 100%	Compatible
4	ROBUS RLA250DTG 3W Min 133W Max	10% - 100%	Compatible
5	ROBUS RCRX200D 200W Max	5% - 100%	Compatible
6	ZANO ZGRIDLED 5W Min 250W Max	25% - 80%	Compatible
7	DETA VR250GR 5W Min 250W Max	10% - 100%	Compatible
8	Schneider GGBL6012LSS 5W Min 100W Max	15% - 100%	Compatible
9	Varilight ZOJP250-P 5W Min 120W Max	20% - 80%	Compatible
10	Click MD9014 5W Min 100W Max	15% - 100%	Compatible
11	Lutron Rania RA2 50W Min 450W Max	10% - 100%	Compatible
12	Rako RMT500 1W Min 500W Max	10% - 100%	Compatible

LED Group

 Western Retail Park
 Nangor Road
 Dublin 12
 Ireland

 T +353 1 709 9000
 F +353 1 709 9060
 IRL Freefax 1800 281 282
 UK Freefax 0800 973 221

 Email info@ledgrouprobust.com
www.ledgrouprobust.com
www.robustdirect.com

Rest of EU

1	ABB 6523 U-102-500 400W Max	20% - 100%	Compatible
2	ABB 6523UR...-103... 400W Max	10% - 100%	Compatible
3	Jung 1270 3W Min 60W Max	15% - 100%	Compatible
4	Jung 1271 3W Min 100W Max	15% - 100%	Compatible
5	NIKO 310-0280X2W-100W 100W Max	20% - 100%	Compatible
6	YOKIS MTV 500E 100W Max	15% - 100%	Compatible
7	Schneider Odace S5-511 40W Min 600W Max	15% - 100%	Compatible
8	Legrand 0670 83 3W Min 75W Max	15% - 100%	Compatible

LED Group

Western Retail Park
Nangor Road
Dublin 12
Ireland

T +353 1 709 9000
F +353 1 709 9060
IRL Freefax 1800 281 282
UK Freefax 0800 973 221

Email info@ledgrouprobust.com
www.ledgrouprobust.com
www.robustdirect.com

Notes:

1. See detailed Dimmer Compatibility Matrices on next page with details of:

- a. No. of lamps tested
- b. Dimming range

✓ = Recommended ✗ = Not recommended - = Out of Range

2. Compatibility is based on fittings and dimmers being operated within manufacturer specifications (e.g. minimum and maximum **LED load** requirements of dimmer are met).

Please ensure to check the relevant dimmer instruction manual.

