KITCHEN & FURNITURE



COMMODORE CIRCULAR AND ROYAL TRIANGULAR 2.5W COB LED, 240V, IP20, CABINET LIGHTS

These cabinet lights provide an excellent replacement for traditional G4 Halogen lamped fittings which require constant replacement of lamps. Available in circular or triangular, they not only look superb, but allow extended operation times due to the low power consumption used compared to traditional G4 Halogen



Applications:

- Inside cabinet displays
- Under or on top of wall cabinet's
- Recessed in stair strings or risers
- Kitchen kick boards
- Reception desk lighting
- Bedroom wardrobes
- Bar shelving

Construction:

Carbon steel and aluminium housing White / Brushed chrome powder coating finish Polycarbonate diffuser Carbon steel bracket FR4 laminate PCB

Features:	Benefits:
-----------	-----------


Manufactured from high quality carbon steel and aluminium with	Excellent aesthetics to enhance the look of any installation		
White or Brushed Chrome powder coat finish	 Strong and durable and won't easily chip if knocked 		
	Choice of colour finish to match or contrast most decors		
Circular or Triangular shape options	Provides a choice of shape to best suit the installation		
Warm white or Neutral white colour temperature options	The light colour can be chosen to compliment the colour and type of		
	items displayed		
Utilises high quality LM80, Chip on Board LED technology	Provides excellent light output comparable to 20W G4 Halogen		
	Uses only 2.5 watts of power for low running costs		
	- Amazingly, around €/£ 0.60 per year @ 5 hours/day, 365 days/yea		
	High efficacy of 83lm/cctW		
	Low running temperature for long life of Halogen		
	- Around 10 times the life of G4 Halogen		
Wide ambient temperature operating range	The fittings will operate in areas that are kept cold or hot such as		
	display cases for items that may deteriorate if exposed to low or high		
	ambient temperatures		
No ultra violet or infra-red in the light beam	Will not fade or damage sensitive display items		
Cool running	Will not burn if touched by children or those with sensitive skin		
Driver integral to the fitting and pre-wired with 1m of 3 core flex	No control gear to mount or hide as with G4 Halogen		
	Direct to mains connection for fast and simple installation		
Detachable mounting base	The head can be semi-recessed, or surface mounted in the base		
Pre-formed base mounting holes	Provides quick and easy installation		





COMMODORE CIRCULAR AND ROYAL TRIANGULAR 2.5W COB LED, 240V, IP20, CABINET LIGHTS

Product Code: White: Brushed Chrome:	Circular	Circular		Triangular	
	RCD2P530-01 RCD2P530-13	RCD2P540-01 RCD2P540-13	NA RYA2P530-13	NA RYA2P540-13	
Comparable to:	20W halogen	20W halogen	20W halogen	20W halogen	
Total Power (W):	2.5	2.4	2.5	2.4	
Total Light Output (lm):	190	210	190	210	
Efficacy (lm / cctW):	83	88	83	88	
Rated Life (hrs):	30,000	30,000	30,000	30,000	
Warranty (yrs):	3	3	3	3	
Illuminance at 1m (lux):	77	79	77	79	
Beam Angle (deg):	110	110	110	110	
CCT (K):	3,000	4,000	3,000	4,000	
CRI (Ra):	80	80	80	80	
Ingress Protection (IP):	20	20	20	20	
Operating Temperature (°C):	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	
Power Factor (PF):	0.9	0.9	0.9	0.9	
Height (mm):	32	32	45	45	
Diameter (mm):	71	71	124	124	
Cut out (mm):	55	55	125	125	
Box Qty:	1	1	1	1	
Weight (kg):	0.17	0.17	0.19	0.19	



Cone Illuminance Diagram:




Diagram for RYA2P540-13 in 4,000K. Other diagrams available on request

Standards & Approvals:

Complies with: EN 55015, EN 61000-3-2, EN 61000-3-3, EN 61547, EN 60598-1, EN 6058-2-1, EN 62471, EN 62493



Polar Intensity Diagram:




Diagram for RYA2P540-13 in 4,000K. Other diagrams available on request

